














tel. 0048 56 686 93 05
 fax 0048 56 686 23 05
 www.elterm.pl





















	EKW AsP 4 ÷ 24 kW
	EKW AsBN 4 ÷ 24 kW
	EKW AsZN 4 ÷ 24 kW
	EKW AsD 4 ÷ 24 kW
	EKW AsZN-W 4 ÷ 24 kW
	EKW AsB/90°C 30 ÷ 144 kW
	ECO Towel Rails 70 ÷ 110 kW
	ECOTERM Heaters 320 ÷ 800 W
	Hydraulic fittings and connections central heating and hot utility water assemblies
	Room controllers
	Pump controllers

EKW boilers are adapted for use with various room controllers and weather compensation units.

Manufacturer reserves the right to introduce structural modifications to the boiler.

EUROSTERS

COMMERCIAL OFFER

	EUROSTER 2000 corded, temp. range 5°-30°C hysteresis 1°C or 2°C, 2 temp. levels		EUROSTER 2000 TX cordless, temp. range 5°-30°C hysteresis 1°C or 2°C, 2 temp. levels		EUROSTER 2000 P floor version, temp. range 5°-30°C hysteresis 1°C or 2°C, 2 temp. levels
	EUROSTER 2006 corded, temp. range 5°-35°C hysteresis 0.4°C or 1°C, 2 temp. levels		EUROSTER 2006 TX cordless, temp. range 5°-35°C hysteresis 0.4°C or 1°C, 2 temp. levels		EUROSTER 2006 P floor version, temp. range 5°-45°C hysteresis 0.4°C or 1°C, 2 temp. levels
	EUROSTER 2020 corded, temp. range 5°-27°C hysteresis 0.5°C, 1°C or 2°C, 4 temp. levels		EUROSTER 2020 TX cordless, temp. range 5°-27°C hysteresis 0.5°C, 1°C or 2°C, 4 temp. levels		EUROSTER 2020 P floor version, temp. range 5°-27°C hysteresis 0.5°C, 1°C or 2°C, 4 temp. levels
	EUROSTER 2510 (16A) corded, temp. range 5°-30°C hysteresis 0.4°C or 1°C, 2 temp. levels		EUROSTER 2510 TX (16A) cordless, temp. range 5°-30°C hysteresis 0.4°C or 1°C, 2 temp. levels		EUROSTER 1310 corded, temp. range 5°-35°C hysteresis 1°C
	EUROSTER 3000 (16A) corded, temp. range 5°-32°C hysteresis 0.5°C or 1°C, 6 temp. levels		EUROSTER 3000 TX (16A) cordless, temp. range 5°-35°C hysteresis 0.5°C or 1°C, 6 temp. levels		EUROSTER 1100 water pump controller
	EUROSTER 1100 B hot utility water pump controller prevents hot utility water from cooling down		EUROSTER 1100 C water pump controller equipped with ANTI STOP		EUROSTER 1100 E central heating pump or hot utility water pump controller
	EUROSTER 1100 K for fireplaces with water jackets central heating pump and water valve controller		EUROSTER 1100 M three-way valve pump controller with limit switches		EUROSTER 1100 W for solid fuel boilers blowing fan and central heating pump controller
	EUROSTER 1100 WB for solid fuel boilers, blowing fan and central heating pump controller, weather compensation system, works with room thermoregulator		EUROSTER 1100 Z central heating and hot utility water pump controller, equipped with independent temp. sensors		EUROSTER 1100 S for a solar system
	BELLUX temperature controller – analogue, corded, temp. range 5° - 30°C				